

Item no. 99550045-02

Adapter type F-81-HQ DUAL GROUNDING BLOCK AU
ACCEPTS PIN Ø 0.4-1.2mm

Frequency Range	0.3 - 3000 MHz
Impedance (Nom.)	75 Ω
Amp. Rating (measured)	4,5 A @10°C increase
	(calculated) 6,3 A @20°C increase
Transfer Impedance (CoMeT)	<0,9 mΩ/m @ 5-30MHz
	<0,03 mΩ/item @ 5-30MHz
Shielding Effectiveness (CoMeT)	>140 dB @ 30-1000MHz
	>120 dB @ 1000-3000MHz

All tests performed using instruments calibrated in accordance to our ISO 9001 certification. Further technical specifications and installation instructions can be obtained on request.



Return Loss (IEC 61169-1)
(Rhode und Schwarz ZVB-8)

0.3 - 500 MHz
500 - 860 MHz
860 - 1000 MHz
1000 - 1750 MHz
1750 - 2150 MHz
2150 - 3000 MHz

	Better than	Typical
0.3 - 500 MHz	-43 dB	-45,0 dB
500 - 860 MHz	-40 dB	-43,0 dB
860 - 1000 MHz	-39 dB	-42,3 dB
1000 - 1750 MHz	-31 dB	-33,5 dB
1750 - 2150 MHz	-29 dB	-31,1 dB
2150 - 3000 MHz	-23 dB	-25,0 dB

Insertion Loss Max.

0.3 - 500 MHz
500 - 860 MHz
860 - 1000 MHz
1000 - 1750 MHz
1750 - 2150 MHz
2150 - 3000 MHz

	Better than	Typical
0.3 - 500 MHz	-0,07 dB	-0,02 dB
500 - 860 MHz	-0,07 dB	-0,02 dB
860 - 1000 MHz	-0,07 dB	-0,02 dB
1000 - 1750 MHz	-0,08 dB	-0,03 dB
1750 - 2150 MHz	-0,09 dB	-0,04 dB
2150 - 3000 MHz	-0,10 dB	-0,05 dB

Temperature

Installing
Operating
Storing

Installing	-5° to +50° C
Operating	-40° to +70° C
Storing	-40° to +70° C

Intermodulation
3rd Order (@2x1W)

IM3	IP3-value
-145 dBc	+92 dBm

Inner Conductor Resistance
(@ 1 A DC)

5 mΩ

Sealing Test
(IEC IP-code)

IP X8 30 meter / 8 hours

Insulation Resistance
(@ 500 VDC)

>200 GΩ

O-rings

-

Dielectric Strength
DC Test Voltage

3 KV

Base Material

Body Parts	Brass CuZn39Pb3 / Zinc
Inner Conductor	Beryllium copper

Max. Tensile Strength
Overall

-

Plating

Body Parts	Nickel
Inner Conductor	Gold

Torsional Strength
(Connector / Cable)

-

Insulators

PE

Test performed by
Date of release

Søren B. Sørensen
March 23, 2011

Remarks

Min. male inner conductor accepted after mating with max. diameter is 0,5mm

ISO 9001:2000 / ISO 14001 certified

Distributor:

CABELCON
connectors

Corning Cabelcon ApS, Industriparken 10, DK 4760 Vordingborg
Tel: +45 55 98 55 99 · Fax: + 45 55 98 55 04
E-mail: cabelcon@cabelcon.dk · www.cabelcon.dk

Form 041 rev 7