

Item no.

Adapter type

<b>Frequency Range</b>	0.3 - 3000 MHz
<b>Impedance (Nom.)</b>	75 Ω
<b>Power Rating</b>	0,1 W
<b>Transfer Impedance (CoMeT)</b>	0,2 mΩ/m @ 5-30MHz
	0,01 mΩ/con. @ 5-30MHz
<b>Shielding Effectiveness (CoMeT)</b>	135 dB @ 30-862MHz

**All tests performed using instruments calibrated in accordance to our ISO 9001 certification. Further technical specifications and installation instructions can be obtained on request.**



**Return Loss**

(RF Analyzer HP 8719D / 8714C)

	Better than	Typical
0.3 - 500 MHz	-22 dB	-24,6 dB
500 - 860 MHz	-18 dB	-20,0 dB
860 - 1000 MHz	-16 dB	-18,8 dB
1000 - 1750 MHz	-12 dB	-14,5 dB
1750 - 2150 MHz	-11 dB	-13,1 dB
2150 - 3000 MHz	-9 dB	-11,4 dB

**Insertion Loss Max.**

	Better than	Typical
0.3 - 500 MHz	-6,3 dB	-6,0 dB
500 - 860 MHz	-6,4 dB	-6,0 dB
860 - 1000 MHz	-6,4 dB	-6,0 dB
1000 - 1750 MHz	-6,7 dB	-6,0 dB
1750 - 2150 MHz	-6,9 dB	-6,0 dB
2150 - 3000 MHz	-7,2 dB	-6,0 dB

**Temperature**

Installing	-5° to +50° C
Operating	-40° to +70° C
Storing	-40° to +70° C

**Base Material**

Body Parts	Brass CuZn39Pb3
Inner	Brass CuZn39Pb3

**Plating**

Body Parts	Nickel
Inner	Tin

**Dielectric Strength**

AC Test Voltage	150 V
-----------------	-------

**O-rings**

**Test performed by**

**Insulators**

**Date of release**

**Remarks**

ISO 9001 certified

Distributor:

